



## Shandong Rhinoceros Engineering Machinery CO., LTD

X80-E specification

With CE certificate

sing YANMAR engine, in-line four strokes, low fuel consumption, environmental protection, convenient repair and maintenance.

Electronic monitoring using a dot matrix type advanced multifunctional large screen liquid crystal display, electronic throttle control system has the function of throttle control, automatic idle speed, overheat protection, speed acquisition.

Give full consideration to reduce the working oil consumption, to obtain maximum efficiency in all kinds of work site operation.

Imported original hydraulic parts, quality is reliable and stable, working efficiency is high.

Based on the strong and durable key parts and international quality chassis configuration, operation stability is stronger.

The machine adopted new type cab with wide field of vision, new seat, and automatic regulated air conditioning system, make the operation flexible and comfortable.

The concept of low noise, ensure the operator to manipulate more comfortable and safety.



Delivery time: within 15 days after received the down payment

Terms of payment: 30% T/T in advance, balance paid before shipment.

Warranty: 1 year.



# Shandong Rhinoceros Engineering Machinery CO., LTD

Detailed specification:

MAIN DIMENSIONS	UNIT	X80-E
( Operating Weight )	kg	8000
( Overall Dimension )	mm	5830x2150x2640
( Cab Dimension )	mm	1300x950x1520
( Bucket Capacity )	cbm	0.3
SYSTEM CONFIGURATION		
( Engine Type )		YANMAR(4TNV94L-SFN)
( Rated Power/Speed )	kw	39.8
( No. of Cylinders/Type )		4 cylinder / in line
( Starting Type )		Electric 12V
( Hydraulic Main Pump )		DOOSAN
( Hydraulic System Pressure )	MPa	22
( Hydraulic System Flow )	L/min	150
( Pilot Pump )		DOOSAN
( Valve )		EATON
( Swing Motor )		EATON
( Max Swing Speed )	r/min	9 r/min
( Travel Motor )		EATON
( Speed )	km/h	H: 3.7km/h ; L: 2.3/km/h
( Bucket Digging Force )	Kn	58
( Arm Digging Force )	Kn	42
( Working Fuel Consumption )	L/h	7.08
( Diesel Oil Tank Capacity )	L	167
( hydraulic Oil Tank Capacity )	L	125
OPERATION RANGE		
( Boom Length )	mm	3300
( Arm Length )	mm	1750
( Radius to Rear End )	mm	1570
( Ground Clearance )	mm	345
( Blade Dimension )	mm	2024x345
( Max Digging Height )	mm	6320

ADD: Dingyuanzhai Industrial Park, 18km east of liaocheng, Shandong Province, China.  
Tel: 0086-635-8362550 Fax: 0086-635-5846000

## Shandong Rhinoceros Engineering Machinery CO., LTD

(Max Dumping Height)	mm	4440
(Max Digging Depth)	mm	3540
(Max Digging Radius)	mm	6240
(Standard Machine With A/C)	A/C	Standard
(Packing Way)		2 units in a 40HQ
(Passed Certificates)		CE ISO

### More photos:

