

HBT30 trailer Concrete Pump**Payment terms**

1.30% by T/T as advance payment with 7days after the contract signed, the balance of 70% by irrevocable L/C at sight.

Delivery Schedule

Delivery should be within 7-10 days from the date of receipt of 30% down payment.

Warrantee

The warranty will be one year from the date of shipment. Any detected parts during this period caused by the quality of products will be replaced by seller free of cost (exclude wear and tear parts), improper operation and other manmade reasons are excluded.



Shandong Rhinoceros Engineering Machinery CO., LTD

Technical parameters:

Model No./Concrete pump	HBT30
Max. theoretical concrete output(m ³ /h)	Low pressure 30/high pressure 16
Max. theoretical concrete pumping pressure(Mpa)	Low pressure 5.5/high pressure 10
Theoretical vertical conveying height(m)	Low pressure 55 /high pressure 130
Theoretical Horizontal transmission distance(m)	350
Allowing the concrete slump(mm)	100-230
Max. Aggregate particles(mm)	30/35
Hopper volume(m ³)	0.45
Filling height(mm)	1100
Rated power(kw)	46
Hydraulic system	Double circuit opening system
Hydraulic oil tank volume(L)	180
The radiator cooling	Air cooling system
Electric control	PLC
Concrete tube conveying diameter(mm)	Φ89/Φ108
Overall dimension(L×W×H)(mm)	4300×1670×1680
Total weight(kg)	3100
Hydraulic pump type	Ram pump