



## Shandong Rhinoceros Engineering Machinery CO., LTD

### Quotation of HBT60 Concrete Pump

#### Payment terms

1.30% by T/T as advance payment with 7days after the contract signed, the balance of 70% by irrevocable L/C at sight.

#### Delivery Schedule

Delivery should be within 20 days from the date of receipt of 40% down payment.

#### Warrantee

The warranty will be one year from the date of shipment. Any detected parts during this period caused by the quality of products will be replaced by seller free of cost (exclude wear and tie parts), improper operation and other manmade reasons are excluded.

#### Technical parameters:

Model No./Concrete pump	HBT60
Max. theoretical concrete put(m <sup>3</sup> /h)	Low pressure 55/high pressure 27
Max. theoretical concrete pumping pressure(Mpa)	Low pressure 4.7/high pressure 9.3
Theoretical vertical conveying height(m)	120
Theoretical level transmission distance(m)	350
Allowing the concrete slump(mm)	100-230
Max. Aggregate particles(mm)	45/40
Hopper volume(m <sup>3</sup> )	0.5
Filling height(mm)	1100
Concrete cylinder diameter × stroke(mm)	Φ200×1800
Main oil cylinder diameter(mm)	Φ100
Max stroke(mm)	1800
Dynamic brand	Diesel engine DEUTZ
Dynamic model	TBD226B-6G



## Shandong Rhinoceros Engineering Machinery CO., LTD

Rated power(kw)	112
Fuel consumption(g/h.kw)	197
Hydraulic system	Double circuit opening system
Brand of main pump	Rexroth
Discharge of main pump(ml)	190
Max. hydraulic system pressure(Mpa)	30
Hydraulic oil tank volume(L)	320
The radiator flow(L/min)	Air cooling system
Electric control	PLC
Concrete tube conveying diameter(mm)	Φ150/Φ133
Max. towing speed(km/h)	15
Overall dimension(L×W×H)(mm)	5100×2160×2600
Total weight(kg)	6000
Type	Ram pump