

4x4 dumper

The engine with strong power is of safety, reliability, good acceleration on start-up, outstanding power performance.

Hydraulic power steering makes the steering convenient, safe and reliable. Adjustable steering wheel can effectively relieve the burden of driver.

Mallery single-top amplification mechanism has great lifting force. The lifting is smooth with stable and reliable performance.

The cab has front tilting design. Easy engine maintenance and repair.

Vehicle model		ZTQ2510CSD
Product positioning: short-distance transportation or agricultural and sideline products and construction materials.		
Working condition: rural roads, pavement of sand/cement roads and mountain roads.		
Engine		
Engine model and emission		QC2105
Engine type		Air cool, in line.
Rated power of engine (kw/rpm)		27
Engine displacement (L)		2.02
Gearbox		
Gearbox type		Manuel 4+1
Gearbox speed ratio		6: 37
Gearbox speed ratio		F: 6.40, 3.09, 1.69. R: 7.82
Dumping type/oll cylinder size		Hydraulic lifting
Cabin type/width		Single-row
Drive form		4x4
Tire type/number		750-16/F:2, R:4.
Brake	Service brake type	Hydraulic braking, drum.
	Parking brake type	Central drum type braking
Steering device		Manual
Weight parameter		
Curb weight(kg)		2250
Rated load capacity(kg)		1110
Performance parameter		
Maximum speed (no load) (km/h)		54
Maximum gradeability (%)		45
Maximum turning radius (m)		11
Maximum lift degree (°)		42
Dimension parameters		
Overall dimensions (LxWxH) mm		4980x1990x2245
Internal cargo body dimensions (LxWxH) mm		2590x1810x400
Wheelbase(mm)		2960
Front/rear wheel track (mm)		1440/1550
Front/rear suspersion(mm)		950/1360

Rated voltage(V)	12
Capacity of the fuel tank(L)	30